



(08) 9451 2204

WWW.TRUFLOWHYDRAULIC.COM.AU
SALES@TRUFLOWHYDRAULIC.COM.AU

CRIMP CHART

			-04 (1/4")	-05 (5/16")	-06 (3/8")	-08 (1/2")	-10 (5/8")	-12 (3/4")	-16 (1")	-20 (1-1/4")	-24 (1-1/2")	-32 (2")		
Hose	Stem	Ferrule												
Low Pressure	CR1	C	CN1	17.90		20.50	23.50	26.60	30.60	38.50	47.50	53.00	66.70	
		G	-	17.90		21.60	25.15	28.60	34.05	44.45				
	G1	GS	GS1F-2								49.80			
		GSP	GSP1F-2									58.40	71.10	
	G1H	G	-	18.30		21.45	25.90	28.85	34.30	44.70	52.05			
		GS	GS1F-2					26.80	32.25	40.65	49.80			
	GTH	G	-	19.05	20.05	21.60	26.30	29.30	35.30	43.45				
	MegaTech 1000	G	-	17.80		20.60	24.90	29.50	33.70	43.20	51.30			
	ACP (MegaTech II)	G	-								53.95			
		GSP	24GSP1F-2									59.95	72.90	
	C5CXH	G	-		18.30	20.45	22.50			35.30	35.30			
		GS	GS1F-4					31.85						
<i>C5C and C5CXH are "non true bore" hoses, please consult the catalogue for stem selection.</i>														
CR2	C	CN2	18.90		21.80	24.40	27.60	31.70	39.50	50.50	59.50	72.90		
	G	-	18.80		22.60	26.65	29.70	35.45	45.20					
EFG3K	GS	GS1F-4								52.05				
	GSP	GSP1F-4									61.95	74.55		
G2H	G	-								53.95				
	GS	GS1F-2								51.80				
	GSP	GSP1F-2									60.05	72.90		
G2XH	G	-	18.80		22.60	26.65	29.70	35.45	44.70	53.95				
	GS	GS1F-2			21.35	23.85	27.45	33.00	41.40	51.80				
	GSP	GSP1F-2									60.05	72.90		
M2T	G	-	18.15	20.20	21.85	26.30	28.60	34.80	43.45	49.80				
	GS	GS1F-2			20.70	23.00	27.20	32.75	38.35					
MXT	G	-	18.15	20.20	21.20	25.15	28.85	34.30	42.80					
	GS	GS1F-2			20.20	23.00	26.55	31.50	38.75					
MXT-XTP	G	-	18.15	20.20	20.90	25.15	28.85	34.30	42.80					
	GS	GS1F-2			20.20	23.00	26.55	31.50	38.75					
High Pressure	EFG4K	GS	GS1F-4			24.90	27.45	33.55	37.60	44.45	52.05			
	EFG6K	GS	GS1F-4			24.90	27.45	33.55	37.60	44.45				
		GS	GS1F-6								56.65			
	MXG4K-XTP	GSM	-									63.75	79.25	
		G	-			21.45	25.90	29.20	34.80					
	<i>MXG4K-XTP with MegaCrimp Couplings is rated to 600,000 impulse cycles. Use MXG4K-XTP with GS Couplings for 1,000,000 impulse cycle rating</i>													
	MXG4K-XTP	GS	GS1F-2			20.70	23.20	27.70	33.25					
		GS	GS1F-4							43.95				
	MXG5K-XTP	G	-			22.00	26.15							
		<i>MXG5K-XTP with MegaCrimp Couplings is rated to 600,000 impulse cycles. Use MXG5K-XTP with GS Couplings for 1,000,000 impulse cycle rating</i>												
		GS	GS1F-2			21.00	23.50		33.25					
	MXG5K-XTP	GS	GS1D1F-4					30.50						
GMV MegaFlex		G	-						37.15	44.00	51.00			
	GSP	GSP									57.05	70.65		
J2AT	G		18.80		22.75									
	GS	GS1F-2			21.35									
STH	CT		12.40		16.60	20.40	22.50	26.72	32.87					
RFS	G	-	17.90		21.45	25.65		34.30	44.70					