



(08) 9451 2204

WWW.TRUFLOWHYDRAULIC.COM.AU

SALES@TRUFLOWHYDRAULIC.COM.AU

CRIMP CHART

Hose	Stem	Ferrule	-04 (1/4")	-05 (5/16")	-06 (3/8")	-08 (1/2")	-10 (5/8")	-12 (3/4")	-16 (1")	-20 (1-1/4")	-24 (1-1/2")	-32 (2")	-40 (2-1/2")	-48 (3")	-64 (4")	
C5CXH	G	-		18.30	20.45	22.50			35.30	44.95						
	GS	GS1F-4					27.70	31.85								
<i>C5C and C5CXH are "non true bore" hoses, please consult the catalogue for stem selection.</i>																
CR1	C	CN1	17.90		20.50	23.50	26.60	30.60	38.50							
	G	-	17.90		21.60	25.15	28.60	34.05	44.45							
G1	G	-								52.05						
	GS	GS1F-2								49.80						
	GSP	GSP1F-2									58.40	71.10				
G1H	G	-	18.30		21.45	25.90	28.85	34.30	44.70	52.05						
	GS	GS1F-2					26.80	32.25	40.65	49.80						
	GSP	GSP1F-2									58.40	71.10				
GTH	G	-	19.05	20.05	21.60	26.30	29.30	35.30	43.45							
MegaTech 500	GSP	GS1F-2									57.40	70.60				
	GL	-									48.65	61.20	71.10	86.60		
MegaTech 1000	G	-	17.80		20.60	24.90	29.50	33.70	43.20	51.30						
ACP (MegaTech II)	G	-								53.95						
	GSP	GS1F-2									59.95	72.90				
CM2TDL	G	-	18.15		21.85	26.30										
	GS	GS1F-2			20.70											
CR2	C	CN2	18.90		21.80	24.40	27.60	31.70	39.50							
	G	-	18.80		22.60	26.65	29.70	35.45	45.20							
EFG3K	GSP	GS1F-4									62.00	74.55				
G2	G	-								53.95						
	GS	GS1F-2								51.80						
	GSP	GS1F-2									60.05	72.90				
G2H	G	-								53.95						
	GS	GS1F-2								51.80						
	GSP	GS1F-2									60.05	72.90				
G2XH	G	-	18.80		22.60	26.65	29.70	35.45	44.70	53.95						
	GS	GS1F-2			21.35	23.9	27.45	33.00	41.40	51.80						
	GSP	GS1F-2									60.05	72.90				
M2T	G	-	18.15	20.20	21.85	26.30	28.60	34.80	43.45	49.80						
	GS	GS1F-2			20.70	23.00	27.20	32.75	38.35							
M3K	G	-	17.80	20.05	20.55	25.40	29.70	35.45	45.70							
	GS	GS1F-2				22.75	27.45	33.00	40.90							
MXT	G	-	18.15	20.20	21.20	25.15	28.85	34.30	42.80							
	GS	GS1F-2			20.20	23.00	26.55	31.50	38.75							
MXT-XTP	G	-	18.15	20.20	20.90	25.15	28.85	34.30	42.80							
	GS	GS1F-2			20.20	23.00	26.55	31.50	38.75							
EFG4K	GS	GS1F-4			24.90	27.45	33.55	37.60	44.45	52.05						
	GS	GS1F-4			24.90	27.45	33.55	37.60	44.45							
EFG6K	GS	GS1F-6								56.65						
	GSM	-									63.75	79.25				
	G	-			21.45	25.90	29.20	34.80								
MXG4K-XTP	<i>MXG4K-XTP with MegaCrimp Couplings is rated to 600,000 impulse cycles. Use MXG4K-XTP with GS Couplings for 1,000,000 impulse cycle rating</i>															
	GS	GS1F-2			20.70	23.20	27.70	33.25								
	GS	GS1F-4							43.95							
MXG5K-XTP	G	-			22.00	26.15										
	<i>MXG5K-XTP with MegaCrimp Couplings is rated to 600,000 impulse cycles. Use MXG5K-XTP with GS Couplings for 1,000,000 impulse cycle rating</i>															
	GS	GS1F-2			21.00	23.85			33.25							
	GS	GS1F-4							44.85							
GMV MegaFlex	G	-							37.15	44.00	51.00					
	GSP	GS1F-2									57.05	70.65				
	GL	-											72.40	87.40	114.35	
J2AT	G	-	18.80		22.75											
	GS	GS1F-2			21.35											
PW6000	G	-			21.20											
RFS	G	-	17.90		21.45	25.65		34.30	44.70							
STH	CT	-	12.40		16.60	20.40	22.50	26.72	32.87							